V30 Pet GPS Tracker

Device Function		Motherboard Technical Parameters	
Operstation System	MTK	GSM Chipset	MTK 2503
GSM、GPRS	Support	GSM band	850/900/1800/1900
GPS Location	Support	GPS/ Beidou combo chip	Built-with Chipset
AGPS	Support	GPRS	Class12
LBS Location	Support	GPS/ Beidou Signal	BD2, 1561.098MHz / L1,1575.42MHz C/A code
Remote upgrade	Support	GPS Channel	22 Channel
Remote Debug	Support	AGPS speed	26s Cold boot
Remote Parameters Setting	Support	GPS/Beidou Sensitivity	Track：-165dBm，Catch：-148dBm
3D G-Sensor	Support	GPS Courrency	5-15m
remove alert	Support	GPS Courrency	100-1000M
WIFI Location	Support	**Standby Current**	≤3 mA
low power consumption	Support	**Operation Current**	≈55mA
Real-time tracking	Support, APP , Web,SMS	**Operation Temperature**	-20～70℃
Historical Trajectory	Support, APP , Web	**Operation Humidity**	5% to 95% No solidification
Setting & Checking via SMS	Support	**Certification**	CCC, FCC
Built-in battery	Support	GPS Antenna	Built in ceramic antenna
SIM card	Support	GSM Antenna	Built in FPC antenna
Blind spot complement	Support		
Drift processing	Support		
Lithium battery charging circuit	Support		
protection circu for battery charging	Support		
LED	Support		
Monitoring function	Support		
Auto repair	Support		
USB port	Support		